

## CERTIFICATE

Certificate No. 2025-004
This is to certify that the products listed below produced by

## Hocheng Corporation

are in compliance with the requirements of nanoMark Product Certification System

I. Company Name: Hocheng Corporation

II. Company Certificate: No.019

III. Address: No. 405, Fude 1st Rd., Bade Dist.,

Taoyuan County 334, Taiwan (R.O.C)

IV. Representative : Chiu, Li-Chien

V. Approved product : Anti-Smudge Sanitary Facilities

VI. Product name, model/specification, approved item number and efficacy: please refer to the Appendix

VII. Date of Certificate Issuance: Jan. 01, 2025

Date of Certificate Expiration: Dec. 31, 2025





## **Appendix**

Certificate No. 2025-004

I. Company Name: Hocheng Corporation

II. Approved product: Anti-Smudge Sanitary Facilities

III. Product name, model/specification, approved item number and efficacy:

Product name	Model / Specification	Approved item number	Efficacy
	C160	00122	In compliance with
	AFC233	00123	
	C239ST	00124	the requirements of
	C301ST	00125	ΓTN-008
	C333AdbST	00126	Verification and Validation Standard on Anti-Smudgy
	C335ST	00127	
0	C660AdbST	00128	Sanitary Facilities I : the
One piece toilet	C800AdbMUST	00129	following
tollet	C840AdbMUST	00130	specifications are
	C899AdbMUST	00131	satisfied,
	C4283AdbST	dbST 00132 (1)The water	contact angle is
	C4286AdbST	00133	higher than
	C4289PAdbST	00134	100°. The residual ratio of
	C5519NAdbMUST	00135	contaminant is
	C6677	00136	less than 1%.
	C41N	00137 The residual	ratio of dense-
	C106NAdb	00138	contaminant is
	C108N	00139 less than 1%.	less than 1%. (2)Durability (scrub
		resistance)	
	C128Adb	00141	test: The contact angle is higher than 100°
	CS130E	00142	
Class savials	CS140E	00143	after 2000
Close-couple toilet	C141N	00144	cycles of
tollet	C142N 00145 res	scrubbing, the residual ratio of	
	C145N	00146	contaminant is less than 1% and the residual ratio of dense contaminant is less than 5%.
	C218	00147	
	CS662Adb	00148	
	CS662A	00149	
	CS802NAdb	00150	
	CS923Adb	00151	

	Product name	Model / Specification	Approved item number	Efficacy
		CS999	00152	
4		CS4272P	00153	In compliance with
		C4288NBPAdb	00154	the requirements of
		CS4384Adb	00155	ΓTN-008
		CS4386AAdb	00156	Verification and Validation Standard
	Close-couple toilet	C4388Adb	00157	on Anti-Smudgy
	tollet	CS4389PAdb	00158	Sanitary Facilities : the
		C4515	00159	following
		C5516PUAdb	00160	specifications are
		C5517PUAdb	00161	satisfied,
		CS5518EAdb	00162	(1)The water contact angle is
		U24	00163	higher than
		U28	00164	100°. The residual ratio of
		U29	00165	contaminant is
		U29N	00166	less than 1%.
		U289	00167	The residual ratio of dense-
	Urinal	U333BAdb	00168	contaminant is
	Ulliai	U660Adb	00169	less than 1%.
		U661	00170	(2)Durability (scrub resistance)
		U800Adb	00171	test : The
		U999	00172	contact angle is higher than 100°
		U448 <mark>5Adb</mark>	00173	after 2000
		U448 <mark>6Adb</mark>	00474	cycles of
		L100	00175	scrubbing, the residual ratio of
		L101Adb	00176	contaminant is
		L102Adb	00177	less than 1%
	Wash Basin	LF103Q	00178	ratio of dense
		L104SAdb	00179	contaminant is
		LF105	00180	less than 5%.
		L107S	00181	

Taiwan Nanotechnology 5300 Industry Development Association



## **Appendix**

Certificate No. 2025-004

I. Company Name: Hocheng Corporation

II. Approved product: Anti-Smudge Sanitary Facilities

III. Product name, model/specification, approved item number and efficacy:

Product name	Model / Specification	Approved item number	Efficacy
	L120S	00182	In compliance with the requirements of
	LF131SAdbR	00183	
	LC134TG	00184	
	LF161SAdbR	00185	「TN-008 Verification and
	L186SAdb	00186	Validation Standard
	L201S	00187	on Anti-Smudgy Sanitary Facilities」: the
	L252S	00188	
	LF257SAdbR	00189	following
	LF259SAdbR	00190	specifications are
	LF320	00191	satisfied,
	L323S	00192	(1)The water contact angle is higher than 100°. The residual ratio of contaminant is less than 1%. The residual ratio of dense-contaminant is less than 1%. (2)Durability (scrub resistance) test: The contact angle is higher than 100° after 2000 cycles of scrubbing, the residual ratio of contaminant is less than 1% and the residual
Wash Basin	L333SAdbR	00193	
	L337N	00194	
	L351	00195	
	L351S	00196	
Wasii Dasiii	LF358SR	00197	
	L363NS	00198	
	LF367SR	00199	
	LF800SAdbR	00200	
,	LF802SAdbR	00201	
	L957S	00202	
	LF964S	00203	
	L970SAdb	00204	
	L3038	00205	
	L4001	00206	
	L4002S	00207	
	L4003S	00208	ratio of dense
	L4006	00209	contaminant is
	L4010	00210	less than 5%.
	L4011	00211	

Product name	Model / Specification	Approved item number	Efficacy
	L4056	00212	
	L4080	00213	In compliance with
	L4112SR	00214	the requirements o
	LF4112SR	00215	ΓTN-008
	LF4113SR	00216	Verification and Validation Standard
	L4122S	00217	on Anti-Smudgy
Wash Basin	LF4140R	00218	Sanitary
	LF4174S	00219	Facilities」: the following
	LF4182SAdbR	00220	specifications are
	LF4185SAdbR	00221	satisfied,
	LF5513NSAdb	00222	(1)The water contact angle is
	L6633SAdb	00223	higher than
	L7080	00224	100°. The residual ratio of
			less than 1%. The residual ratio of dense- contaminant is less than 1%.
			(2)Durability (scrub resistance) test: The contact angle is higher than 100° after 2000 cycles of scrubning, the residual ratio of
			escutarinant is less than 17% and the residual ratio of dense contaminant is less than 5%.

Taiwan Nanotechnology 5300 Industry Development Association 5